

METHOD AND DEVICE FOR CANCELING NOISE

Publication number: JP2003008521 (A)

Publication date: 2003-01-10

Inventor(s): KAKO TAKASHI; OKITA RYOJI +

Applicant(s): FUJITSU LTD + (FUJITSU LTD)

Classification:

- international: G10L15/20; G10L21/02; H04B1/10; H04B1/12; H04B3/54; H04B15/02; H04J11/00; H04J13/00; H04L27/00; H04L27/26; H04L27/34; H04R3/02; G10L15/00; G10L21/00; H04B1/10; H04B1/12; H04B3/54; H04B15/02; H04J11/00; H04J13/00; H04L27/00; H04L27/26; H04L27/34; H04R3/02; (IPC1-7): H04L27/00; H04B15/02; G10L15/20; G10L21/02; H04B3/54; H04J13/00; H04R3/02

- European: H04B1/10E2; H04B1/12; H04B1/12A; H04L27/26M5

Application number: JP20010186276 20010620

Priority number(s): JP20010186276 20010620

Also published as:


JP3427381 (B2)
US2003002590 (A1)
US7113557 (B2)
EP1303094 (A2)
EP1303094 (A3)

more >>

Abstract of JP 2003008521 (A)

PROBLEM TO BE SOLVED: To provide a method and device for canceling noise for power line carrier communication or the like that adaptively selects a band to an actual noise to cancel noise and enhances the S/N to enable high-speed communication. SOLUTION: A zero point insert section 27-2 inserts a zero point signal to prescribed positions of signals sent from a transmission signal generating section 27-1 and the resulting signal is sent to a transmission line 27-3. A receiver side uses an interleave section 2-13 to extract a noise component from the zero point signal, uses a noise distribution identification section 2-11 to identify a noise distribution from a silence signal period of a received signal, a noise prediction section 2-15 extracts a greater frequency band of the noise components having frequencies in pairs generated by the insertion of the zero point signal according to a comparison result by a pair frequency estimate power comparison section 2-12 to predict noise. A subtractor section 2-16 eliminates the predicted noise from the received signal to cancel the noise.

本発明の録音信号処理装置は、雑音キャンセリングの機能を持つ。



Data supplied from the **espacenet** database — Worldwide